

PROFESSIONAL BRAND



DISCOS FLAP

SECUR®

Características:

- Disco de desbaste y pulido
- Acero / Madera
- Óxido de Aluminio



ISO 9001

Código	Medida (mm)	Medida (")	Grano	Tipo	Velocidad tangencial máx.	Velocidad máx.
416030	115 x 22,23	4 1/2x 7/8	40	27	13.300 RPM	80m/seg.
416032	115 x 22,23	4 1/2x 7/8	60	27	13.300 RPM	80m/seg.
416034	115 x 22,23	4 1/2x 7/8	80	27	13.300 RPM	80m/seg.
416036	115 x 22,23	4 1/2x 7/8	100	27	13.300 RPM	80m/seg.
416038	115 x 22,23	4 1/2x 7/8	120	27	13.300 RPM	80m/seg.

Acero / Madera



PROFESSIONAL BRAND



DISCOS FLAP

SECUR®

Características:

- Disco de desbaste y pulido
- Acero / Acero inox.
- Óxido de Zirconio

2^{en}1



ISO 9001

Código	Medida (mm)	Medida (")	Grano	Tipo	Velocidad tangencial máx.	Velocidad máx.
416040	115 x 22,23	4 1/2x 7/8	40	27	13.300 RPM	80m/seg.
416042	115 x 22,23	4 1/2x 7/8	60	27	13.300 RPM	80m/seg.
416044	115 x 22,23	4 1/2x 7/8	80	27	13.300 RPM	80m/seg.
416048	115 x 22,23	4 1/2x 7/8	120	27	13.300 RPM	80m/seg.

Acero / Acero INOX.

